

**DIPARTIMENTO DI INGEGNERIA  
CORSO DI DOTTORATO IN INGEGNERIA INDUSTRIALE E  
DELL'INFORMAZIONE -  
PHD COURSE IN INDUSTRIAL AND INFORMATION ENGINEERING -  
36TH CYCLE**

Title of the research activity:	<p>Microwave <u>S</u>ensors for <u>H</u>ydraulic <u>M</u>onitoring and IoT Applications (<b>MiSeHM</b>)</p> <p>Scientific field: ING-INF/01 – Electronics</p>
State of the Art:	<p>Microwave sensors like radars and radiometers are complex electronic apparatuses, historically adopted for remote-sensing and imaging purposes. The firsts (radars) are active sensors used to detect objects of different nature, to measure their distance and relative velocity (by the Doppler effects) and to locate or identify them. The seconds (radiometers) are passive sensors that reveal the microwave black-body radiation of the matter and, through this principle, they are capable to measure, in a contactless way, the (brightness) temperature of objects. Furthermore, since various molecule and atom resonances occur in the microwave range, microwave radiometers can identify specific substances such as the water vapor in the atmosphere. In addition, the long wavelength microwaves can penetrate through cloud cover, haze, dust, and even rain. Finally radiometers are at the heart of radio-telescopes and radioastronomy and the nowadays knowledge of the universe is also based on their discoveries: from the Cosmic Background Radiation (CMB) to the atomic hydrogen in stellar clouds and nebula.</p> <p>Despite the widespread usage of radar and radiometers in ground and space-based platforms, their potential is not yet fully exploited in drones. The impressive advances of the radio-frequency hardware, mostly due to the progress of silicon microelectronic technologies, allow a new class of ultra-miniaturized radar/radiometer sensors to be conceived. These could be on-board drones to allow a number of exciting applications: monitoring the water level and surface velocity of rivers, early detection of forest fire, pollution monitoring, precision agriculture and many other.</p> <p>Among these scenarios, the hydraulic monitoring of rivers is of particular relevance since these sensors</p>

	<p>can be adopted, in a IoT infrastructure, for floods prevention and risk management. The next challenge, indeed, is the extensive monitoring of rivers and, to this purpose, the unit cost of radar (radiometric) sensors should be reduced by one order of magnitude, i.e. from thousand to hundred euro. Since the most expensive item is the antenna, low-cost technologies (like planar technologies) have to be accepted in the sensor design at the expenses of some performance degradation.</p> <p>The present Ph.D. research aims at exploring these novel possibilities: from the hardware conception of the sensors to their on-field exploitation. It will be carried-out within the National Research project <i>“IntEractions between hydrodyNamics flows and bioTic communities in fluvial Ecosystems: advancement in dischaRge monitoring and understanding of Processes Relevant for ecosystem sustalnability by the development of novel technologieS with fIeld observatioNs and laboratory testinG”</i> (ENTERPRISING), funded in 2019 by MIUR.</p>
<p>Short description and objectives of the research activity:</p>	<p>The primary objective of the present Ph.D. research is to develop, experimentally validate and demonstrate on board drones a miniaturized, multi-mode radar/radiometer sensor equipped with frequency scanning antenna. The two basic ideas are: i) since radars and radiometers share most of the front-end devices and electronics, a multi-mode sensor can be devised in such a way to increase miniaturization; ii) a frequency scanning antenna array can be used in both cases to provide an imaging capability without the complex (and costly) electronic of a phased array.</p> <p>Along this line there are several open problems, requiring a deep investigation. The major open issues from the radar point of view are: modeling of FMCW radars with frequency scanning antennas; development of leakage cancel circuits in the FMCW mode; noise caused in the Doppler mode by the drone blades and its reduction; data processing in order to reconstruct the image. The major open issues from the radiometer point of view are: modeling of microwave radiometers with frequency scanning antennas; singal processing of the radiometer data and image reconstruction; new calibration circuitry. Novel and original results are expected for each of the above issues.</p>
<p>Bibliography:</p>	<p>1. F. Alimenti et al., "Noncontact Measurement of</p>

River Surface Velocity and Discharge Estimation With a Low-Cost Doppler Radar Sensor," in IEEE Transactions on Geoscience and Remote Sensing, doi: 10.1109/TGRS.2020.2974185.

2. C.A. Schuetz, C. Harrity, G.J. Schneider, J. Murakowski, S. Shi, J. Deroba, D.W. Prather (2018). A Promising Outlook for Imaging Radar. IEEE MICROWAVE MAGAZINE, vol. 19, n. 3, pp.91-101.
3. F. Alimenti, V. Palazzi, C. Mariotti, M. Virili, G. Orecchini, S. Bonafoni, L. Roselli, P. Mezzanotte (2017). A 24-GHz radar front-end integrated on a multilayer cellulose-based substrate for Doppler radar sensors. SENSORS, vol. 17, p. 1-17, ISSN: 1424-8220, doi: 10.3390/s17092090
4. T. Geibig, A. Shoykhetbrod, A. Hommes, R. Herschel, N. Pohl (2016). Compact 3D imaging radar based on FMCW driven frequency-scanning antennas. IEEE Radar Conference, 2016, pp. 1-5.
5. W. Mayer, M. Wetzel, W. Menzel (2003). A Novel Direct-Imaging Radar Sensor with Frequency Scanned Antenna. IEEE International Microwave Symposium Digest, 2003, pp. 1941-1944.
6. W. Plant, W. Keller, and K. Hayes, "Measurement of river surface currents with coherent microwave systems," IEEE TRANSACTIONS ON GEOSCIENCE AND REMOTE SENSING, vol. 43, no. 6, pp. 1242–1257, Jun. 2005, ISSN: 0196-2892.
7. M. Ferrick, N. Yankielun, and D. Nelson, "A doppler radar for continuous remote measurement of river ice velocity," US Army Corps of Engineers, Cold Regions Research & Engineering Laboratory (CRREL), Report 95-21, 1995.
8. S. Bonafoni, F. Alimenti, L. Roselli (2018). An Efficient Gain Estimation in the Calibration of Noise-Adding Total Power Radiometers for Radiometric Resolution Improvement. IEEE TRANSACTIONS ON GEOSCIENCE AND REMOTE SENSING, pp. 1-10, ISSN: 0196-2892, doi: 10.1109/TGRS.2018.2812904
9. L. Aluigi, D. Pepe, F. Alimenti, D. Zito (2017). K-Band SiGe System-on-Chip Radiometric Receiver for Remote Sensing of the Atmosphere. IEEE TRANSACTIONS ON CIRCUITS AND SYSTEMS. I, vol. 64, p. 3025-3035, ISSN: 1549-8328, doi: 10.1109/TCSI.2017.2761703

	<p>10. F. Alimenti, S. Bonafoni, L. Roselli (2017). A novel sensor based on a single-pixel microwave radiometer for warm object counting: Concept validation and IoT perspectives. SENSORS, vol. 17, ISSN: 1424-8220, doi: 10.3390/s17061388</p> <p>11. G. Tasselli, F. Alimenti, S. Bonafoni, P. Basili, L. Roselli (2010). Fire Detection by Microwave Radiometric Sensors: Modeling a Scenario in the Presence of Obstacles. IEEE TRANSACTIONS ON GEOSCIENCE AND REMOTE SENSING, vol. 48, p. 314-324, ISSN: 0196-2892, doi: 10.1109/TGRS.2009.2024305</p> <p>12. F. Alimenti, S. Bonafoni, S. Leone, G. Tasselli, P. Basili, L. Roselli, K. Solbach (2008). A Low-Cost Microwave Radiometer for the Detection of Fire in Forest Environments. IEEE TRANSACTIONS ON GEOSCIENCE AND REMOTE SENSING, vol. 46, p. 2632-2643, ISSN: 0196-2892, doi: 10.1109/TGRS.2008.921395</p>
Scientific coordinator (s)	Dr. Federico Alimenti (Local coordinator of the ENTERPRISING PRIN project)
Contact (s)	<a href="mailto:federico.alimenti@unipg.it">federico.alimenti@unipg.it</a>